



**NATURAL**



**WITH GAS**



**WITH LITTLE GAS**



**AMBIENT TEMPERATURE**

## GREEN WITH TO KM 0

### ✓ INNOVATIVE

- The new sanitation systems and UVC lamp make mains water more pleasant

### ✓ ECO-SUSTAINABLE

- Water Km 0 means: less air pollution, less CO2 emissions, and less plastic production. The bag in box is a packaging that guarantees a high degree of hygiene and respect for the environment in the disposal. LED lighting.

### ✓ QUALITY

- SINGLE automatic vending machine with sanitizing process of the product pick-up area and the whole interior.
- SINGLE with bottle / container sanitization process (PATENTED)
- Always fresh water, not permanent for a long time in the plastic, great to drink .

### ✓ MODEL MASTER/SLAVE

- Master version distributor.
- Master slave wiring for payment system applied to another vending machine .
- Slave wiring for payment system ap
- 

## TOUCH

For selection product

## BOX SANITIZED

EVERY 20 MINUTES



## DELIVERY

Water  
Sanitation

## PAYMENT SYSTEMS

Coins  
Cashless  
Master / Slave with  
any distributor

## CHANGE



## TECHNICAL FEATURES

**LEDA** is the **ONLY** vending machine with area sanitization procedure product withdrawal and all its interior, it is easily connected to the water supply, it is able to supply fresh water at any time, reducing it waste, promote ECO-SUSTAINABLE behaviors, reduce management costs and has a very low environmental impact.

- **PRODUCTS: 5**
- **SELECTIONS 16: glass 0,20 water bottles lt, 0,50lt, 0,75lt, 1lt**
- **COLD NATURAL WATER**
- **COLD WATER WITH GAS**
- **COLD WATER WITH LITTLE GAS**
- **NATURAL WATER AMBIENT TEMPERATURE**
- **BOTTLE SANITIZATION**
- **Display: Touch screen 7"** which can provide all information regarding the use of the distributor.

## MACHINE MANAGEMENT

- Sanitization of the product withdrawal area through OZONE
- Sanitization of the entire inside of the machine using OZONE
- Sanitization bottle through ozonated water process (PATENTED system)
- Powder activated carbon filter (PAC) capable of retaining all impurities up to 0.5 microns in size, eliminating all odors and flavors such as those of dissolved chlorine, asbestos fibers and some microorganisms such as "cryptosporidium"
- Sterilization of water using a new generation UV-C lamp
- Destroys bacteria on the water spout
- Alarms: flooding, waste liquid level
- Programming of liters of water filter
- Water filter replacement signal
- Payment system: Parallel 12 or 24 V, Serial with protocol Executive, MDB, Master and Slave

## TECHNICAL DATA

- Water production 40 l / h - Ice bank
- Dimensions: height 163 cm, width 54,5 cm, depth 63 cm
- Weight: 80 kg
- Voltage: 230V – 50Hz
- Refrigerant system: Ecological Gas R 134A
- Water mains pressure: between 2 to 3.5 Bar (attack JG 8)

## ACCESSORIES

- Co2 cylinder      Kit exchange cylinder CO2
- Hot water Kit    anti-flood kit

