

THE NEW WAY OF DRINKING WATER AT HOME OR IN THE OFFICE, WITHOUT PLASTIC BOTTLES

QI Cabinet is the above-counter solution, with an elegant, silent and compact design. Ideal for serving microfiltered water, at room temperature and cold (QI Easy), and cold sparkling water (QI Bubble). It is available in black and white, with a front panel entirely made of tempered glass for an elegant design.







We are an innovative company that pays attention to sustainability. We address those who consider water a precious resource, which should not be wasted but enhanced.

Q1 EASY

Q1 BUBBL

MICROFILTERED WATER



Ambient



Cold

MICROFILTERED WATER



Ambient





Cold sparkling

2 VERSIONS



White Precoated metal sheet





Black Precoated metal Sheet



1 Cabinet

DESIGN, FUNCTIONALITY E PERFORMANCE

Tempered glass front panel, backlit buttons and thin stainless steel headboard give it a unique and elegant design, perfect for the home and office environment. Thanks to its narrow shape and small dimensions, QI Cabinet is the right solution for saving space, without sacrificing performance: the ice bank cooling system and cold carbonation keep the temperature and carbonation level of the water constant provided.

HYGIENE AND PEACE OF MIND

The internal components in direct contact with water are located in a protected space and are made entirely of stainless steel in order to guarantee maximum antibacterial action.





INSTALLATION AND SIMPLICITY

Q1 Cabinet takes up very little space and is silent. Installation is simple and performance guaranteed.


A CUSTOMIZABLE SYSTEM THAT MEETS EVERY NEED

With Q1 Under you can choose the cooler that best suits your needs



| Dimensions | 200 (L) x 844 (P) x 1142 (H) |
|-------------------------|---|
| Technology | Ice bank |
| Ice bank | 4,3 L capacity |
| Types of water | Ambient, chilled, sparkling, Not |
| Test conditions | 20°C incoming water and 25°C room temperature |
| Performance | 30 L per hour; 6 L continuously < 12°C |
| Boiler | 0,5 L, 1200 W - temperature 98° C |
| Usage recommendation | Home, Small Office, bar: 1 - 20 people |
| Carbonator | Stainless steel carbonator , 0,5 L capacity |
| Carbonation Pump | Membrane pump |
| Refrigeration gas | R 290 |
| Compressor | 1/12 HP - 220/230 V 50 Hz |
| Thermostat | Mechanical |
| Condensation | Dynamic ventilation |
| Coils | 6 mm stainless steel |
| Ø Water inlet | 8 mm |
| Ø C02 Inlet | 6 mm |
| Ø Fill Ice bank | 8 mm |
| Water inlet pressure | not over 3 bar - recommended reducer |
| CO2 inlet pressure | Ideal pressure: in between 3,5 - 4,5 bar |
| Finish | Housing skinplate, front glass or glazed aluminum |
| Power Supply | 230 V - 50 Hz |
| Weight | 32 Kg |
| Flow regulator | Included (into the unit) |
| Filtration | Not included |
| Water pressure reducers | Not included |
| CO2 pressure reducers | Not included |
| Led Lamp UV-C | Not included |
| | <u> </u> |

REAR VIEW



SIDE VIEW





TAPS CABINET

